#### **Solar Probe Plus**

A NASA Mission to Touch the Sun

#### Integrated Science Investigation of the Sun Energetic Particles



# Preliminary Design Review 05 – 06 NOV 2013

# **EPI-Hi Sensor Design**

Mark Wiedenbeck

EPI-Hi Lead Co-I (JPL)

This document contains technical data that may be controlled by the International Traffic in Arms Regulations (22 CFR 120-130) and may not be provided, disclosed or transferred in any manner to any person, whether in the U.S. or abroad, who is not 1) a citizen of the United States, 2) a lawful permanent resident of the United States, or 3) a protected individual as defined by 8 USC 1324b(a)(3), without the written permission of the United States Department of State.



#### Outline



- Measurement Requirements
- Sensor System Overview
- Low-Energy Telescopes
- High-Energy Telescope
- Solid-State Detectors
- Species and Energy Coverage and Energy Binning
- Element Resolution
- Helium Isotope Identification
- Electron Identification
- Fields of View
- Angular Sectoring
- Measurement Cadences
- Dynamic Range in Particle Intensities
- Redundancies: Design for Graceful Degradation
- Additional Capabilities: Bonus Science Opportunities
- Peer Review Results
- Summary

## **EPI-Hi Measurement Requirements**

- Protons and Heavy lons
  - Energy range: 1 MeV/nuc (TBR) to ≥50 MeV/nuc
  - Energy binning: ≥6 bins per decade
  - Cadence: at least one energy bin with time resolution of 5 s or better
  - FoV:  $\geq \pi/2$  sr in sunward and anti-sunward hemispheres (incl. 10° from S/C-Sun line)
  - Angular sectoring: ≤30° sector width
  - Composition: at least H, He, C, O, Ne, Mg, Si, Fe, <sup>3</sup>He
  - Species resolution: FWHM ≤ 0.5 (TBR) × separation from nearest abundant neighbor
  - Max intensity: up to 10% (TBR) of upper limit proton spectrum from EDTRD
- Electrons
  - Energy range: 0.5 MeV (TBR) to ≥3 MeV
  - Energy binning: ≥6 bins per decade
  - Cadence: at least one energy bin with time resolution of 1 s or better
  - FoV:  $\geq \pi/2$  sr in sunward and anti-sunward hemispheres (incl. 10° from S/C-Sun line)
  - Angular sectoring: ≤45° sector width
  - Max intensity: up to 10% (TBR) of upper limit electron spectrum from EDTRD\*

\*Note: upper limit electron spectrum not yet specified in EDTRD

# EPI-Hi Sensor System Overview (1/2)



- Sensor Approach
  - All sensor elements are silicon solid-state detectors
  - Multiple detector telescopes to provide large energy range and sky coverage
  - · Some telescopes double-ended to increase sky coverage
  - Detector segmentation to provide angular sectoring and adjustable geometrical factor
- Heritage
  - Numerous energetic particle instruments over the past 40 years
  - Direct predecessor: STEREO/LET & HET
- Key Differences
  - Thinner detectors and windows to reduce energy threshold
  - Compact telescope designs to reduce saturation at high particle intensities and backgrounds at low intensities



## EPI-Hi Sensor System Overview (2/2)



#### **3 detector telescopes:**

 1 double-ended low-energy telescope (LET1)

SIS

- 1 single-ended low-energy telescope (LET2)
- 1 double-ended high-energy telescope (HET)
- All sensor elements are ion-implanted silicon solid-state detectors
- Signals from each telescope processed by an individual electronics board





# High-Energy Telescope



**Conceptual Cross Section** HET (double ended) 90° H1A -H2A — H3A — H4A **— H5A — H5B** — H4B — НЗВ -H2B -H1B 1 cm

windows (each end): 2 × 127 µm Kapton

color: active silicon grey: inactive material





#### Species and Energy Coverage and Energy Binning



- Rates are accumulated on-board in logarithmically spaced energy bins of width of a factor of 2<sup>1</sup>/<sub>2</sub> or 2<sup>1</sup>/<sub>4</sub>
- Bin width of 2<sup>1</sup>/<sub>2</sub> corresponds to ~6.6 bins per decade
- Larger bins are used for some rates accumulated at the highest cadence (1 second) in order to increase statistical accuracy



#### **Element Resolution**





- Energy loss measurements from the detector in which a particle stops (E') and the preceding detector (ΔE) organize the data into distinct tracks for the various elements.
- Sector information is used to obtain mean thickness penetrated in the ΔE detector and make an onboard correction to the measured energies to optimize species resolution.
- Energy assigned on-board includes energies measured in overlying detectors and calculated energy loss in windows.



- Monte Carlo simulation of He isotope resolution: example based on L1A vs. L2A
- Resolution dominated by effect of incidence angle uncertainty on  $\Delta E$  thickness penetrated
- Restricting analysis to narrow-angle sectors gives higher resolution dataset
- Other effects (e.g., channeling) limit measurable <sup>3</sup>He/<sup>4</sup>He ratio at energies of a few MeV/nuc to >~5%

# **Electron Identification**



Example: measurements from the STEREO/HET telescope in the 13 Dec 2013 SEP event 250 Histogram 200 10 150 1Hgol 2 10 von Rosenvinge et Heal., Space Sci. 100 Rev., 136, 391, 2008 10 50 10 0 100 50 logH2 H5 electrons



- EPI-Hi HET uses a 500 µm front detector vs. 1000 µm in STEREO/HET
- High-energy electrons should deposit ~0.17 MeV in H1 and be detectable using the modeled 0.11 MeV threshold
- Once electronic noise level has been measured in a realistic setup, we will assess whether a modest increase in the H1 thickness is desirable







Five 45° - Half-Angle View Cones



#### **Angular Sectoring**



Locations of Centers of Angular Sectors, Telescope Axis at Center of Diagram



- Particle directions of incidence are determined based on active elements hit in two positionsensitive Si detectors (L0 and L1, L1 and L2, or H1 and H2)
- Each of these detectors has central bull's eye surrounded by 4 quadrants
- Area of each active element is 0.2 cm<sup>2</sup>
- Quadrants in the second detector rotated 45° about the telescope axis relative to those in the first detector
- 25 combinations of hit elements in the two detectors are used to assign event to a viewing sector
- For an isotropic distribution of particles, ≥80% of the particles detected in a sector have directions of incidence within 15° of the mean viewing direction of the sector
- Significant overlap among sectors allows measurements of particle distributions with angular resolution smaller than the size of a sector
- HET provides sectored electron data, LET1 provides only front-back direction information for electrons

### **Measurement Cadences**



- Highest cadence: 1 second
  - Used for one electron bin below and one above 1 MeV
  - Used for 4 proton bins above 1 MeV
- Intermediate cadence: 10 sec
  - Used for narrow energy bins for e, H, He, <sup>3</sup>He
  - Used for intermediate-width energy bins for element groups CNO, NeMgSi, Fe
- Normal cadence: 60 sec
  - Used for narrow energy bins for <sup>3</sup>He, and major elements from C through Ni
  - Used for wide energy bins for groups of ultraheavy elements
- Low cadence: 300 sec
  - Used for angular distribution of e, p, He, <sup>3</sup>He, CNO, NeMgSi, and Fe in intermediate energy bins
- Very low cadence: 1 hr
  - All rates accumulated at cadences of 60 sec and 300 sec are also accumulated over 1 hr

# Dynamic Range in Particle Intensities (1/2)



- Protons and He dominate the EPI-Hi count rates and the associated dead-time
- A "dynamic threshold" system, successfully used in the LET and HET instruments on STEREO, allows the adjustment of the geometrical factor for protons and He while maintaining the full geometrical factor for Z≥6 elements
- In several stages, thresholds are raised on all but one active element in detectors progressively deeper in the stack to suppress protons and He over a portion of the instrument geometrical factor
- A detector element that remains sensitive to protons and He is used to monitor the actual rate so that thresholds can be returned to the lower values (with some hysteresis) when particle intensities have decreased
- Count rates at which thresholds are dynamically raised and lowered are controlled by entries in the command table

# Dynamic Range in Particle Intensities (2/2)

- An estimate of the distribution of SEP event sizes was obtained by combining: 1) an extensive database of SEP observations at 1 AU, 2) the radial dependence of peak intensities derived from Lario et al. (2007), and 3) the SPP orbit
- ~50 events are expected inside 0.25 AU over the 7-year mission, including ~2 "severe" events and possibly an "extreme" event
- Both HET and LET use dynamic thresholds when intensities exceed ~2000 /cm<sup>2</sup>sr-s



# Redundancies: Design for Graceful Degradation



- The radiation and dust environments close to the Sun are poorly known and may be severe.
- The front detectors, particularly in the LETs, have minimal shielding in order to achieve a low energy threshold and are thus particularly vulnerable to damage by radiation and dust.
- The normal instrument coincidence logic defines some categories of events that do not require a signal from an L0 detector, so failure of an L0 detector would increase the LET telescope threshold but otherwise not interfere with instrument operation.
- The coincidence equations can be redefined in order to optimize performance in the event of other detector failures. For example, if an H1 detector were to fail, the HET coincidence could be redefined to accept events based on detectors deeper in the stack and allow measurements with poorer angular and energy resolution.
- The double-ended telescopes have separate bias supplies for the two ends to preserve functionality in the event of a bias failure.
- Resistors in series with detectors allow a limited number of shorted detectors without compromising the operation of an entire telescope end.

#### Additional Capabilities: Bonus Science Opportunities



EPI-Hi lends itself to several measurements without requiring modifications of the hardware design:

- Ultraheavy (UH) elements: PHASIC dynamic range allows measurements of groups of elements with atomic numbers Z≥30. Large enhancements of UH elements are sometimes observed in impulsive SEP events.
- <sup>22</sup>Ne/<sup>20</sup>Ne isotope ratio measurements: this isotope ratio has been observed to be enhanced by factors ~5 in some impulsive events.
- Neutral particles including gamma-rays, neutrons, and energetic neutral atoms (ENAs): HET should be capable of measuring gammas and neutrons in some large SEP events. LET should be able to identify ENA hydrogen originating from charge exchange between SEP protons and ambient H atoms in the corona.





## **Peer Review Results**



A combined peer review of the sensor system and front-end electronics (PHASIC) design was held on 1 March 2013 to address the suitability of this combination for making the required measurements. External (non-EPI-Hi) reviewers: Rick Leske (Caltech), Matt Hill (APL), Mihir Desai (SwRI).

Significant Issues Raised and Responses or Actions Taken:

- 1) If the instrument experiences large temperature variations, electronic thresholds, gains, and offsets could change enough to require updating parameters used for the on-board analysis during a solar encounter. <u>Response/Action</u>: Temperature variation over the SPP orbit has been evaluated and found to be less than the ~10°C that would require adjusting on-board analysis parameters.
- 2)Large dynamic range could lead to significant cross-talk and possibly retriggering, as experienced on STEREO/LET. <u>Response/Action</u>: Design improvements going from the STEREO PHASIC to the SPP PHASIC had already been implemented to reduce retriggering and to flag crosstalk. Details are given in the presentation on the EPI-Hi electronics.



#### Summary



- EPI-Hi builds on heritage from the STEREO/LET and HET instruments to provide a combination of sensor system and electronics capable of meeting the requirements of Solar Probe Plus
- Significant new features include:
  - The development of thin silicon detectors to reduce the EPI-Hi energy threshold and achieve some overlap with EPI-Lo
  - Compact packaging of detector stacks to reduce backgrounds and improve performance under conditions of high particle intensities
  - Addition of small detector segments ("small pixels") that can be used to provide a measure of proton intensities under extreme conditions
  - Enhancement of capabilities for on-board analysis including He isotope identification and multiple measurement cadences to optimize the use of available telemetry